



Cellular Confinement Systems - Geocell

EnviroTendon

Our EnviroTendon is used to anchor our EnviroGrid on steep slope applications as well as chanel. The type and break strength of the EnviroTendon is based on specific job site peramiters.



12626 North Houston Rosslyn Rd.
Houston, TX USA 77086
Phone: (281) 820-5493
Fax: (281) 820-5499
www.geoproducts.org

EnviroTendon	Material	Break Strength	Nominal Width	Coil Length	Coil Weight
PT2200	Polyester	2200 LB (9.34 kN)	3/4 inch (19 mm)	1,650 FT (503 m)	16 LBS (7.3 kg)
PT3285	Polyester	3,285 LB (14.5 kN)	1 1/8 inch (28.57 mm)	600 FT (183 m)	15 LBS. (6.8 kg)
PT5100	Polyester	5,100 LB (23.2 kN)	1 1/4 inch (31.75 mm)	835 FT (255 m)	26 LBS. (11.8 kg)
PT7700	Polyester	7,700 LB (35 kN)	1 5/8 inch (41.2 mm)	670 FT (204 m)	27 LBS. (12.25 kg)
PT11000	Polyester	11,000 LB (50 kN)	1.625 inch (41.3 mm)	670 FT (204 m)	44 LBS (21.8 kg)
PT16500	Polyester	16,500 LB (75 kN)	2 inch (50.8 mm)	500 FT (152.4 m)	48 LBS. (21.8 kg)

THIS PRODUCT CONFORMS TO ASTM DESIGNATION: D 3950; STANDARD SPECIFICATION FOR STRAPPING, NONMETALLIC; TYPE IA, GRADE 2.



07/18



This information is provided for reference purposes only and is not intended as a warranty or guarantee. Geo Products, LLC assumes no liability in connection with the use of this information. Check with Geo Products, LLC for current, standard minimum quality assurance procedures.